

DUPLICATE

Rec'd PCT/PTO

25 APR 2005

10/532797

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/049783 A1

(51) International Patent Classification⁷: A01G 9/24

(74) Agents: JORIO, Paolo et al.; c/o Studio Torta S.r.l., Via Viotti, 9, I-10121 Torino (IT).

(21) International Application Number:
PCT/IT2003/000769

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:
24 November 2003 (24.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
T02002A001037
29 November 2002 (29.11.2002) IT

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): C.R.F. SOCIETA' CONSORTILE PER AZIONI [IT/IT]; Strada Torino, 50, I-10043 Orbassano (IT).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): LO PRESTI, Giulio [IT/IT]; Via Silvio Pellico, 52, I-55049 Viareggio (IT). MENARDI, Luca [IT/IT]; Via Tetto Bovis, 20, I-12020 Madonna Dell'Olmo (IT).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: GREENHOUSE AND METHOD OF CULTIVATION UNDER GLASS



(57) Abstract: A greenhouse (1) is provided with an air humidifier (10) and a condenser ((35): the humidifier (10) has a semi-permeable membrane, of the type which permits the passage of water vapour between opposite sides of the membrane if there is a vapour pressure gradient between the said sides. A flow of sea water (13) and a flow of air (14) taken from the outside are supplied to the humidifier (10) and sent to opposite sides of the membrane, in such a way that the flow of air (14) is humidified before being introduced into the greenhouse; the humidified air (30) is then condensed in the condenser (10) to produce condensate (36) to be used for irrigating the plants.

WO 2004/049783 A1

GREENHOUSE AND METHOD OF CULTIVATION UNDER GLASS

5 TECHNICAL FIELD

The present invention relates to a greenhouse and to a method of cultivation under glass.

BACKGROUND ART

As is known, greenhouses are closed environments,
10 usually delimited by glazed walls, where plants are cultivated in special climatic conditions.

When greenhouses are installed in regions with a particularly dry and arid climate, the cultivation of most plants requires a considerable input of irrigation
15 water, the provision of which can be a major problem in arid regions.

In coastal areas, it has been proposed that suitably desalinated sea water be used for irrigation: however, since the quantity of water required is usually
20 large, as mentioned above, the installations required to produce fresh water from sea water are relatively complicated, expensive and bulky, and are therefore not suitable, for example, for the production of small greenhouses which are self-sufficient in terms of their
25 fresh water requirement.

DISCLOSURE OF INVENTION

An object of the present invention is therefore to provide a greenhouse and a cultivation method applicable to this greenhouse which enable the aforementioned
5 problems to be overcome.

In particular, an object of the invention is to provide a greenhouse having an air humidifier which, by increasing the humidity of the air within the greenhouse, makes it possible to reduce the quantity of
10 irrigation water required for the plants.

Another object of the invention is to provide a greenhouse which has an irrigation system in which the water required for irrigation is obtained, in a simple and economical way, from sea water.

15 The present invention therefore relates to a greenhouse and to a method of cultivation under glass as specified in the attached Claims 1 and 13 respectively.

Preferred embodiments of the greenhouse and of the method of cultivation according to the invention are
20 also specified, in dependent Claims 2 to 12 and 14 to 23 respectively.

The greenhouse according to the invention and the method of cultivation made possible by this greenhouse resolve the aforementioned problems of the prior art.
25 This is because the air introduced into the greenhouse

has a high relative humidity, which may reach approximately 90%, and, if required, a temperature which may be significantly lower than the external temperature: in these conditions, the quantity of water
5 required to irrigate the plants is considerably reduced. Moreover, the irrigation water is obtained, in a simple and economical way, from the sea water which is also used to humidify the air. Consequently, the greenhouse requires no external inputs of fresh water.

10 BRIEF DESCRIPTION OF THE DRAWINGS

Further characteristics and advantages of the present invention will be made clear by the following description of a non-restrictive example of embodiment of the invention, with reference to the figures of the
15 attached drawings, in which:

- Figure 1 is a schematic view of a greenhouse made according to the invention;
- Figure 2 is an enlarged schematic view of a humidifier used in the greenhouse of Figure 1;
- 20 - Figure 3 is an enlarged schematic view of a detail of the humidifier of Figure 2;
- Figure 4 is an enlarged partial schematic view of a condenser used in the greenhouse of Figure 1.

BEST MODE FOR CARRYING OUT THE INVENTION

25 With reference to Figure 1, a greenhouse 1

comprises a structure 2 delimiting a growing environment 3 in which plants 4 are placed. The structure 2 comprises lateral walls 5 which rise vertically from the ground, and a roof 6.

5 The greenhouse 1 comprises an air humidifier 10 and supply means 11 and 12 for bringing a flow of water 13 and a flow of air 14 respectively to the humidifier 10.

With additional reference to Figures 2 and 3, the humidifier 10 comprises at least one exchange element 15
10 having a semi-permeable membrane 16 which is of a known type and which allows water vapour to pass between its opposite sides 17 and 18, through the said membrane, if there is a vapour pressure gradient between these sides 17 and 18.

15 In particular, the membrane 16 which is used is of the type which allows the water vapour to pass in one direction only, but which retains the sea salts and other substances; if, therefore, the sides 17 and 18 of the membrane 16 are in contact, respectively, with a
20 saline aqueous solution, for example sea water, and with a flow of air of low relative humidity, water vapour passes from the saline aqueous solution to the air flow, as shown schematically in Figure 3.

Good results have been obtained by using
25 polypropylene (PP) membranes having a water vapour

resistance RET (determined according to UNI EN 31092) in the range from approximately 2 to approximately 5, preferably from approximately 3 to approximately 4, and in particular in the region of approximately $3.4 [10^{-2}$
5 mbar $m^2/W]$. It should be understood that other known membranes having similar characteristics to those quoted can be used.

In the non-restrictive present case which is illustrated, the humidifier 10 comprises a frame 20
10 which supports the membrane 16, this membrane 16 being shaped in such a way as to form a plurality of compartments 21, constituting corresponding exchange elements 15; each exchange element 15 is delimited by a portion of membrane 16 interposed between the flow of
15 water 13 (sea water), circulating within the exchange element 15, and the flow of air 14, which is in contact with the exterior of the exchange element 15.

The frame 20 is accommodated in an open-ended housing 22 formed in a wall 5a of the greenhouse 1, and carries, at its opposing upper and lower ends
20 respectively, an intake guide 23, which distributes the flow of water 13 to the exchange elements 15, and an outlet guide 24, which collects the water which has passed through the exchange elements 15.

25 The supply means 11 comprise a hydraulic circuit 25

provided with a circulation pump 26 to carry the flow of water 13 to the humidifier 10 and, in particular, into the exchange elements 15.

The hydraulic circuit 25 comprises an intake line 5 25 and an outlet line 28, positioned, respectively, up-line and down-line from the humidifier 10, and connected, respectively, to the intake guide 23 and to the outlet guide 24 of the humidifier 10. The flow of water 13 supplied to the humidifier 10 is a flow of salt 10 water, particularly sea water or brackish water, drawn from the sea at a suitable depth by means of the hydraulic circuit 25.

The supply means 12 comprise forced ventilation means 29 for carrying the air flow 14 to the humidifier 15 10 and for introducing humidified air 30 into the greenhouse 1; in the present case, the forced ventilation means 29 comprise a fan 31 by means of which the flow of air 14 is taken from outside the greenhouse 1 and sent, through a delivery duct 32, to the 20 humidifier 10 and, in particular, sent to make contact with the exterior of the exchange elements 15.

The greenhouse 1 also comprises a condenser 35 for condensing the water vapour present in the humidified air 30 introduced into the greenhouse 1, to obtain 25 condensate 36.

The condenser 35 comprises at least one heat exchange element 37 between the humidified air 30 taken from the growing environment 3 and a cooling fluid 38 having a temperature lower than the temperature of the humidified air 30.

In the present, non-restrictive, case illustrated in Figure 1, and in greater detail in Figure 4, the condenser 35 is incorporated in a wall 5b of the greenhouse 1, opposite the wall 5a provided with the humidifier 10: the condenser 35 and the humidifier 10 are therefore located at opposite ends of the greenhouse 1.

The wall 5b has at least one wall portion 39 having a cavity 40 in which the cooling fluid 38 circulates; the cooling fluid 38 suitably consists of a portion of the flow of water 13 taken up-line from the humidifier 10 and sent into the cavity 40 through a branch circuit 41; the branch circuit 41 is connected to the intake line 27 of the hydraulic circuit 25 by a connector 42. The cavity 40 is provided with an intake 43 and an outlet 44, positioned at opposite ends 46 and 47 respectively, located respectively at the top and the bottom, of the wall portion 39, for the cooling fluid 38.

An inner face 50 of the wall portion 38, facing the

interior of the greenhouse 1, forms a heat exchange surface between the cooling fluid 38 circulating in the cavity 40 and the humidified air 30 present within the greenhouse 1 (in other words in the growing environment
5 3).

At the upper end 46 of the wall portion 39 and above the heat exchange surface 50 there is positioned a suction hood 51 provided with a fan 52 to create a forced circulation of air within the greenhouse 1 and,
10 specifically, to carry the humidified air 30, introduced into the growing environment 3 through the humidifier 10, to the condenser 35, in other words into contact with the heat exchange surface 50. The hood 51 is connected by a recirculation duct 53 to the delivery
15 duct 32.

At the lower end 47 of the wall portion 39 there is positioned a collector 54 to collect the condensate 36 which has formed on the exchange surface 50 and has fallen downwards under the effect of gravity; the
20 collector 54 is connected to an irrigation system 55 of any known type (which, for the sake of simplicity, is not described or illustrated in detail) by a duct 56.

The greenhouse 1 is used for the application of the method of cultivation according to the invention as
25 described below.

The flow of water 13 is taken from the sea and sent to the humidifier 10 by the hydraulic circuit 25; the flow of air 14 is drawn in from the outside and supplied to the humidifier 10 by the fan 31: the vapour pressure
5 of the flow of air 14 is lower than the vapour pressure of the flow of water 13, and therefore water vapour passes in the humidifier 10 from the flow of water 13 to the flow of air 14 through the membrane 16.

Advantageously, the flow of water 13 is supplied to
10 the humidifier 10 at a temperature lower than the temperature of the flow of air 14, in such a way as to cool, as well as humidify, the flow of air 14; the cooling of the flow of air 14 is further promoted by the latent heat of evaporation of the said flow of air 14.

15 The humidified air 30 introduced into the greenhouse 1 is moved by the fan 52 and brought to the condenser 35: the heat exchange between the humidified air 30 and the cooling fluid 38, whose temperature is lower than the temperature of the humidified air 30,
20 causes the condensation of the water vapour present in the humidified air 30 on the exchange surface 53; the resulting condensate 36 is fresh water, which is collected by the collector 54 and sent to the irrigation system 55.

25 Any condensate 36 in excess of the amount required

for irrigation can be drawn off by a branch 58 and stored or sent for other uses.

The fans 29 and 52 cause a forced circulation of the air in the greenhouse 1: the steps of humidification
5 and condensation are therefore essentially carried out continuously and simultaneously in the humidifier 10 and in the condenser 35 respectively, at the opposite ends of the greenhouse 1.

After giving up some of its humidity, the air
10 leaving the condenser 35 has a water vapour content in excess of that of the outside air and a relatively low temperature, and it is therefore recirculated by means of the recirculation duct 53 to the humidifier 10. In a possible variant which is not illustrated, this air,
15 before being recirculated to the humidifier 10, is sent into a cavity formed under or within the roof 6, in such a way that it has a cooling and thermally insulating effect on the said roof 6.

A flow of salt water 60 with a high saline
20 concentration is taken from the humidifier 10, and can be sent, for example, to a salt production plant, or to another desalination device for producing additional fresh water.

Finally, it is clear that the greenhouse and method
25 of cultivation under glass described and illustrated

herein can be modified and varied in numerous ways without departing from the present invention as defined in the attached claims.

CLAIMS

1. Greenhouse (1) comprising a structure (2) delimiting a growing environment (3), and an air
5 humidifier (10), the greenhouse being characterized in that the said humidifier (10) comprises at least one exchange element (15) having a semi-permeable membrane (16), which allows water vapour to pass between opposite
10 sides (17, 18) of the membrane if there is a vapour pressure gradient between the said sides, and in that the greenhouse also comprises first and second supply means (11, 12) for bringing a flow of water (13) and a flow of air (14) respectively into contact with the said opposite sides of the membrane.

15 2. Greenhouse according to Claim 1, characterized in that the said first supply means (11) comprise a hydraulic circuit (25) for bringing the said flow of water (13) into contact with a first side (17) of the membrane (16).

20 3. Greenhouse according to Claim 1 or 2, characterized in that the said flow of water (13) is a flow of sea water.

4. Greenhouse according to one of Claims 1 to 3, characterized in that the said second supply means (12)
25 comprise forced ventilation means (29) for bringing the

said flow of air (14) into contact with a second side (18) of the membrane (16) and introducing the humidified air (30) leaving the said humidifier (10) into the greenhouse.

5 5. Greenhouse according to one of the preceding claims, characterized in that the said humidifier (10) comprises a plurality of exchange elements (15), each exchange element (15) being delimited by a portion of semi-permeable membrane (16) interposed between the said
10 flow of water (13), circulating within the exchange element (15), and the said flow of air (14), which is in contact with the exterior of the exchange element (15).

 6. Greenhouse according to Claim 5, characterized in that the said semi-permeable membrane (16) is shaped
15 in such a way as to form a plurality of compartments (21) constituting corresponding exchange elements (15), the compartments (21) having the said flow of water (13) running within them and having the said flow of air (14) in contact with their exteriors.

20 7. Greenhouse according to one of the preceding claims, characterized in that it comprises a condenser (35) for condensing the water vapour present in the humidified air (30) introduced into the greenhouse and for obtaining condensate (36).

25 8. Greenhouse according to Claim 7, characterized

in that the said condenser (35) and the said humidifier (10) are positioned at opposite ends of the greenhouse, forced ventilation means (29, 52) being provided to keep the air in forced circulation between the said ends of
5 the greenhouse.

9. Greenhouse according to Claim 7 or 8, characterized in that the said condenser (35) is connected to irrigation means (55) for distributing the condensate (36) to the plants placed in the greenhouse.

10 10. Greenhouse according to one of Claims 7 to 9, characterized in that it comprises recirculation means (53) for recirculating the air leaving the condenser (35) and supplying it to the humidifier (10).

11. Greenhouse according to one of Claims 7 to 10,
15 characterized in that the condenser (35) comprises at least one heat exchange element (37) between the humidified air (30) taken from the greenhouse and a cooling fluid (38) having a temperature lower than the temperature of the humidified air (30) within the
20 greenhouse.

12. Greenhouse according to Claim 11, characterized in that it comprises a branch circuit (41) for taking the said cooling fluid (38) from the said flow of water (13) up-line from the said humidifier
25 (10).

13. Method of cultivation under glass, characterized in that it comprises the steps of:

- providing a greenhouse (1) with an air humidifier (10) comprising at least one exchange element (15) having a semi-permeable membrane (16) which allows water vapour to pass between opposite sides (17, 18) of the membrane if there is a vapour pressure gradient between the said sides;
- humidifying a flow of air (14) by the exchange of water vapour between a flow of water (13) and the said flow of air, the flow of air and the flow of water being brought into contact with opposite sides (17) and (18) respectively of the membrane (16);
- introducing the humidified air (30) leaving the humidifier (1) into the greenhouse.

14. Method according to Claim 13, characterized in that it comprises a step of causing a forced circulation of the air in the greenhouse.

15. Method according to Claim 13 or 14, characterized in that the said flow of air (14) is supplied to the humidifier (10) with a vapour pressure lower than the vapour pressure of the said flow of water (13).

16. Method according to one of Claims 13 to 15, characterized in that the said flow of water (13) is

supplied to the said humidifier (10) at a temperature lower than the temperature of the said flow of air (14).

17. Method according to one of Claims 13 to 16, characterized in that the said flow of water (13) is a
5 flow of sea water.

18. Method according to one of Claims 13 to 17, characterized in that it comprises a condensation step, in which the water vapour present in the humidified air (30) introduced into the greenhouse is condensed in a
10 condenser (35) to produce condensate (36).

19. Method according to Claim 18, characterized in that the said condensation step comprises a step of heat exchange between the humidified air (30) taken from the greenhouse and a cooling fluid (38) having a temperature
15 lower than the temperature of the said humidified air.

20. Method according to Claim 19, characterized in that the said cooling fluid (38) is taken from the said flow of water (13) up-line from the said humidifier (10).

20 21. Method according to one of Claims 18 to 20, characterized in that the said humidification step and the said condensation step are carried out in an essentially continuous and simultaneous way at opposite ends of the greenhouse.

25 22. Method according to one of Claims 18 to 21,

characterized in that it comprises a step of irrigating the plants placed in the greenhouse with the condensate.

23. Method according to one of Claims 18 to 22, characterized in that it comprises a recirculation step,
5 in which the air leaving the condenser (35) is collected and supplied to the humidifier (10).

24. Method according to one of Claims 18 to 23, characterized in that the air leaving the condenser (35) is sent to cool a roof (6) of the greenhouse.




Fig. 1




Fig.2




Fig.3




Fig.4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IT 03/00769

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A01G9/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A01G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 34 23 574 A (HENSSLER GMBH & CO KG GEWAECHS) 2 January 1986 (1986-01-02) the whole document	1,4,13, 14
A	FR 2 752 613 A (BOTTLANDER WILFRIED) 27 February 1998 (1998-02-27) page 15, line 2 - page 16, line 32; figure 3	1,4,13, 14
A	DE 33 27 896 A (IMMLER VOLKER) 21 February 1985 (1985-02-21) claims; figures	1,13
	----- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

16 March 2004

Date of mailing of the international search report

23/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Merckx, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IT 03/00769

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>DATABASE WPI Section Ch, Week 199832 Derwent Publications Ltd., London, GB; Class D15, AN 1998-375704 XP002239269 & RU 2 099 289 C (KASHEVAROV YU B) 20 December 1997 (1997-12-20) abstract</p>	1,13
A	<p>DE 33 32 499 A (WESTERN PROMOTIONS LTD) 11 April 1985 (1985-04-11) the whole document</p>	1,13

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IT 03/00769

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
DE 3423574	A	02-01-1986	DE	3423574 A1	02-01-1986
FR 2752613	A	27-02-1998	FR	2752613 A1	27-02-1998
DE 3327896	A	21-02-1985	DE	3327896 A1	21-02-1985
RU 2099289	C	20-12-1997	RU	2099289 C1	20-12-1997
DE 3332499	A	11-04-1985	DE	3332499 A1	11-04-1985